



ODAN 3109 SUBMERSIBLE PETROL / DIESEL HOSE

DESCRIPTION

Black flexible submersible hose for fuel in engine applications. High resistance to all media listed below and especially used as in-tank hose in Car, Truck, Agricultural and Construction equipment vehicles for fuel injection systems.

Normally installed using crimped ferrules or petrol hose clips. Suitable for petrol, diesel, ethanol, gasoline, oxidized sour gas, oil and bio-diesel.

Peak temperature: +150°C.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no. 3109

ApplicationDiesel, Fuel hoseStandard length50 metresWorking temp. $-30^{\circ} \text{ C to } 125^{\circ} \text{ C}$

 Inside compound
 ECO

 Inside colour
 Black

 Outside compound
 ECO

 Outside colour
 Black

 Reinforcement
 PVA

Standards SAEJ30:2022 R10

Std. branding -

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
7,9	14,0	7	34	25	165	3109008000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Pubber Broducts)

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances. End of life evaluation for production of Rubber hoses with Textile reinforcement