



NYLON SLEEVE (HOOK AND LOOP)

TEXWRAP is a foldable sleeve made of polyamide fibers coated on one side with UV-resistant PU. The exclusive locking system, made of highly resistant VCO (Velcro) allows to obtain a tubular protection of endless length and easy to assemble.

TEXWRAP can be supplied in customized versions: cut to size and stitched, with the addition of eyelets and locking catch to improve tear resistance.

Standard colour:

Black - Other colours are available on request.

Temperature range:

-40° C to +180° C (-40° F to +356° F)

MSHA approval for mining applications n. IC207/02

Volume resistivity

(applied voltage 500V) $\Omega \text{ m } 5.9 \cdot 10^{12}$ according to CEI 15-23

Surface resistivity (applied voltage 500V) $\Omega 1.4 \cdot 10^{16}$ according to CEI 15-23

TEXWRAP is available in the following range:

Part. Nr.	Round diameter mm	Coil length mm	Quantity per box m	Availability
TEXW-35	35	50	150	Stock
TEXW-50	50	50	150	Stock
TEXW-75	75	50	100	Stock
TEXW-100	100	50	50	Stock
TEXW-125	125	50	50	Stock
TEXW-150	150	50	50	Stock
TEXW-175	175	50	50	Stock
TEXW-200	200	50	50	Stock

Rolls of 50 m.



Example of customized version with eyelets