

# Codan 3122 Fuel Hose



## Codan 3122 - SAE J30 R6,R7, R8, R11 - 2022

Flexible, black hose for leaded and unleaded petrol. Good ozone resistance. Resistant to oil spray in engine compartments. For fuel pipes in cars, lorries, lawn mowers, garden cultivators, etc. The hose is based on SAE J30 R6, R7, R8, R11 (2022) Acc. EN228:2012 + A1:2017 and EN590:2022. Please contact Codan for further information.

**Type nr.** 3122  
**Application:** Fuel / Diesel  
**Standard Length:** 50 metres  
**Working Temperature:** -40°C to 135°C  
**Inside:** NBR  
**Colour:** Black  
**Reinforcement:** Polyester  
**Outside:** CPE  
**Colour:** Black  
**Standards:** SAE J30 R6,R7, R8, R11 - 2022  
**Std. branding:** -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	10,8	5	50	33	111	3122004000
4,8	11,6	5	50	35	122	3122005000
5,6	12,6	5	50	37	140	3122056000
6,3	13,3	5	50	40	150	3122006000
7,6	14,6	5	50	43	170	3122008000
9,5	16,5	5	50	49	198	3122010000
11,5	18,5	5	50	55	223	3122011500
12,0	19,0	5	50	57	236	3122012000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Mail: [info@codan.com](mailto:info@codan.com)  
[www.codan.com](http://www.codan.com)