

# Nobra Agri

## Rubber zuig- persslang Grieks profiel



Product Name								
Water suction hose G-corrugated								
Description								
Flexible water suction hose for use in agriculture and construction sites, commonly used with liquid manure pumps								
Product Code	ID	OD	Working Pressure	Bursting Pressure	Max. Vacuum	Bending Radius	Weight	Length
	mm	mm	bar	bar	bar	mm	kg/m	m
WTG018Z-50x6.5	50	63 (±1,2)	6	18	0,9	150	1,54	20 & 40
WTG018Z-75x7	75	89 (±1,2)	6	18	0,9	225	2,42	20 & 40
WTG018Z-100x7	100	114 (±1,2)	6	18	0,9	300	3,32	20 & 40
WTG018Z-127x8	127	143 (±1,2)	6	18	0,9	318	4,98	20 & 40
WTG018Z-152x8	152	168 (±1,2)	6	18	0,9	380	6,02	20 & 40
WTG018Z-203x10.5	203	224 (±1,6)	6	18	0,9	508	10,43	20 & 40
Inner tube		Reinforcement			Cover			
SBR Black, smooth, resistant to waste water from 5 to 10 pH		High tensile textile cord, galvanized steel helix			SBR Black, G-corrugated with cloth impression, weather, ozone and abrasion resistant			
Packaging		Temperature			Hose ends			
Coils with PE Wrapping		-30 °C to +85 °C			-			

# Arbon